

EMERGENCY - SIMPLE TROLLEY 100 SERIES 1222 R

DIMENSIONS 640 x 480 mm

ADEQUATE HEIGHT, ERGONOMICS 1005 mm (work surface – floor).

WORK SURFACE

- Polyethylene, PE. Asepsis, hygiene, easy-to-clean.
- Withstands alcohol, detergents, disinfectants, chlorhexidine.
- Protection on all 4 sides. Pleasant to the touch, rounded shapes.

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Fine satin finish, asepsis, hygiene.

ISO DRAWER FRAMEWORK

- Total opening.
- Steel ball-bearing slides with self-closing system.
- Front stop, it protects the slide against strong impacts when closing.
- Load capacity per drawer: 20 kg.
- Interior frame ISO 600 x 400 mm.
- Polyethylene drawer front part, thickness 10 mm, 6 colours (Ref. G, Y, W, B, F, R).
- Ergonomic handle.
- Card holder with white cards, removable.

ISO DRAWERS 600 x 400 mm

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

EXTENSIVE MOBILITY TROLLEYS, DAILY CONDUCTION

- Elevated push handle. Ergonomics, height 1045 mm.
- Double wheels Ø 125 mm. Soft tread, silent.
- 2 antistatic (electrical conductive), 2 with brake at push handle side.



1222 R

165 R.12.14.26D(RA5.A5).28.32R.34.36.40.46.50

ACCESSORIES

12 MANUAL LOCKING

14 NUMBERED DISPOSABLES SEALS - 100 units

26D(RA5.A5) BINS DISPENSERS - CENTRAL SUPPORT

28 ROTATING ARM

32R SIDE SUPPORT

34 CARDIAC MASSAGE BOARD

36 GAS BOTTLE STAND

40 SERUM HOLDER

46 3 GLOVES BOX HOLDER

50 13 LITRES BIN