

TRANSPORT TROLLEYS - TROLLEY WITH ISO PANELS 606 DN.(8)TR.(6)72.(2)73

DIMENSIONS 640 x 480 mm
HEIGHT 1655 mm

MONOBLOC STRUCTURE

- Stainless steel AISI-304. Fine satin finish, asepsis, hygiene.

ISO PANELS

- Flexible organisation inside the trolley.

ISO DRAWERS 600 x 400 mm

- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

2 DOORS

- Total opening 270°.
- Phenolic, 10 mm thickness.
- Lock with 4 keys.
- Card holder with white cards, removable, left door.
- DN Light grey.
- DB Light blue.

VERTICAL HANDLES

- 2 left side, 2 right side.

EXTENSIVE MOBILITY TROLLEYS, DAILY CONDUCTION

- Dual lock wheels Ø 125 mm. Soft tread, silent.
- 2 antistatic (electrical conductive). 2 with brake at the right side of the trolley.
Pedal position: Superior - fixed wheel, easy driving.
Central - swivel wheel.
Inferior - locked wheel.



606 DN.(8)TR.(6)72.(2)73

ACCESSORIES

(8)TR RETENTION STOPS

(6)72 ISO DRAWERS 100 mm

(2)73 ISO DRAWERS 200 mm